

HYDROCARBON MOBILITY ENHANCER

HME-100

FLOWBACK SURFACTANT


HME-100 is a cost-effective, high performance hydrocarbon mobility enhancer designed for use in water based fracturing fluids. This product is used to prevent emulsions that can cause formation damage, as well as reduce surface and interfacial tension downhole for enhanced production. HME-100 alters formation wetabillity from oil to water-wet to further enhance flowback.

SURFACE TENSION

INTERFACIAL TENSION

	Dyne/cm
CONTROL	78. 0
HME-100	34.5

	Dyne/cm
CONTROL	34. 2
HME-100	3.3







This information is provided for general purposes only and is believed to be accurate at the time of publication. Hybrid Chemical Technologies and its affiliates do not make any warranties or representations of any kind regarding the information and disclaim all express and implied warranties or representations to the fullest extent permissible by law, including those of merchant ability, fitness for a particular purpose or use, title, non-infringement, accuracy, correctness or completeness of the information provided herein. All information is furnished 'as is' and without any license to distribute. The user agrees to assume all liabilities related to the user of or reliance on such information. HYBRID CHEMICAL TECHNOLOGIES SHALL NOT BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, PUNITIVE, EXEMPLARY OR CONSEQUENTIAL DAMAGES FROM ANY CAUSE WHATSOEVER INCLUDING BUT NOT LIMITED TO ITS NEGLIGENCE.